



A brand of **TOTAL**

ELF EVOLUTION 900 FTX 5W-30



Top performance motor oil using ELF fully synthetic technology, intended for lubricating gasoline passenger car engines



APPLICATIONS

- Most recent technology engines**
 - Recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi-valve and turbo-charge technologies
- Vigorous driving, all times of year**
 - Meets needs of the motor manufacturers regarding extended oil change intervals
- Even in very severe conditions**
 - Suitable for all types of service (urban, highway or motorway) especially in very severe conditions

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications API SN; ILSAC GF-5

CUSTOMER BENEFITS

- Fuel Economy** Promoted fuel saving
- Excellent engine protection** Excellent start-up performance, prevents sludge build-up and controls oxidation
- Optimal performance** Optimum power and performance under most severe driving conditions
- Low emission vehicles** Fully compatible with all gasoline emission control devices

CHARACTERISTICS

	Method	Units	SAE Grade 5W-30
Density at 15°C	ASTM D1298	Kg/m ³	850
Viscosity at 40°C	ASTM D445	mm ² /s	57
Viscosity at 100°C	ASTM 445	mm ² /s	10
Viscosity index	ASTM D2270	-	160
Pour point	ASTM D97	°C	-36
Flash point	ASTM D92	°C	235

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF EVOLUTION 900 FTX 5W-30

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.